



IPN W880 DECT/GAP/USB

Technical Specifications

Approvals	:	EN60950-1, EN301489-1, EN301489-6, EN55022, EN55024, EN61000-3-2, EN61000-3-3, EN301406v.2.1.1, EN50360:2001 for headset, EN50385 for base
Battery type	:	Li-Ion polymer (replaceable)
Charging temperature	:	0°C to 40°C (32°F to 104°F)
Charging time	:	1 hour
Compatibility	:	DECT/GAP VOIP/USB (Windows 98, 2000, XP Vista, 7, 8 & Mac OS X) compatible
Conference call	:	Up to 3 persons
Dimensions	:	Headset: 20mm (D) x 145mm (L) x 28mm (W) Base: 95mm (D) x 135mm (H) x 49mm (W)
Extra battery charging possibility	:	Yes, in headset base station
Microphone	:	Background noise cancelling microphone
Mute function	:	Yes
Operating frequency	:	From 1880 to 1900 MHz (European Standard)
Operating range	:	400 meters max. / 1300 feet max.
Operation temperature	:	0°C to 40°C (32°F to 104°F)
Pairing passkey or pin	:	By registering the W880 to a DECT Phone , the PIN code of the base unit should be 1111 or 0000
Power Saving	:	Switching Power Mode Supply Dynamic Power Adjustment (strength of the DECT signal is adjusted by the base, dependant on the proximity of the headset to the base)
Rain shower proof	:	No
Security	:	DECT protocol
Speaker	:	High Performance mini-speaker
Stand by time	:	104 hours
Storage temperature	:	0°C to 40°C (32°F to 104°F)
Talk time	:	6,5 hours
Warranty	:	2 years
Waterproof	:	No
Wide band functionality	:	Yes
Weight headset(with battery)	:	28 grams
Weight (without battery)	:	21 grams
Weight battery	:	7 grams
Weight headband	:	18 grams
Weight ear hook	:	3 grams
Wearing styles	:	Ear hook, Head band