

## IPN W9xx DECT/GAP/USB (EU) Technical Specifications

Approvals	:	EN60950-1, EN301489-1, EN301489-6, EN55022, EN55024, EN61000-3-2, EN61000-3-3, EN301406v.2.1.1, EN50360:2001 for headset, EN50385 for base
Battery type	:	Li-lon polymer (replaceable)
Bluetooth (W990)	:	Version 4.1
Bluetooth Range (W990)	:	30 feet
Charging temperature	:	32°F to 104°F (O°C to 40°C)
Charging time	:	1 hour
Compatibility	:	DECT/GAP VOIP/USB (Windows 98, 2000, XP Vista, 7, 8,10 & Mac OS X) compatible
Conference call	:	2 persons
Dimensions	:	Headset Base: 50mm(D) x 110mm(H) x 110mm(W)
Microphone	:	Background noise cancelling microphone
Mute function	:	Yes
Operating frequency	:	From 1880 to 1900 MHz
Operating range	:	150 meters max. / 500 feet max.
Operation temperature	:	O°C to 40°C (32°F to 104°F)
Pairing passkey or pin	:	By registering the W9xx to a DECT Phone , the PIN code of the base unit should be 1111 or 0000
Power Saving	:	Switching Power Mode Supply Dynamic Power Adjustment (strength of the DECT signal is automatically adjusted by the base, dependant on the proximity of the headset to the base)
Protection (Acoustic shock)	:	Yes (92 dB)
Rain shower proof	:	No
Security	:	DECT 6.0 (Step A enhanced security)
Speaker	:	High Performance wideband speaker
Stand by time	:	104 hours
Storage temperature	:	O°C to 40°C (32°F to 104°F)
Talk time	:	9 hours
Warranty	:	2 years
Weight headset (with battery)	:	50 grams (W980)
Weight (without battery)	:	46 grams (W980)
Weight battery	:	4 grams
Wearing styles	:	Ear hook, Head band